



# 480

## PEDESTAL ADHESIVE

**Akfix 480** is a single component, polyurethane based adhesive particularly designed for **installation of access flooring systems.**

### FEATURES & BENEFITS

- Provides excellent green strength,
- Bonds Metal to Concrete,
- Suitable for both indoor and outdoor applications,
- Water resistant when cured,
- Excellent gap-filling properties,
- Paste like consistency,
- One component, no mixing required,
- Good adhesion on concrete, chipboards, plywood, fiber reinforced gypsum and cement boards

### APPLICATIONS

- Suitable for adhesion of raised access floor pedestals to floors
- Suitable on metal, concrete, chipboards, plywood, fiber reinforced gypsum and cement boards.

### INSTRUCTIONS

- Surfaces to which pedestals are to be bonded must be clean, dry, free of dust, dirt, paint, oils, wax and any other foreign matter.
- Apply adhesive to pedestal by the method normally used by a professional installer of access flooring.
- The application temperature must be between +50°C and +35°C. Fresh adhesive can be cleaned with acetone

### RESTRICTIONS;

- Storage above 35 °C may shorten the shelf life
- Should be tested before application for specific substrates

Installation of  
Access Flooring  
Systems



## STORAGE AND SHELF LIFE;

12 months between 5 and 25 °C in closed original packaging.

## SAFETY & DISPOSAL

Contains Diphenylmethane-4,4 di-isocyanide. Corrosive and irritating to eyes, skin and lungs. Harmful if swallowed. Wear chemical resistant gloves and eye protection when in contact. Keep container tightly closed when not in use. Prevent spillages.

## PROPERTIES

<b>Basis</b>	: Polyurethane prepolymer
<b>Density</b>	: 1.42 ± 0.03 gr/ml
<b>Tack-Free Time</b>	: 15± 5min. (at 23°C and %50 R.H.)
<b>Consistency</b>	: Thixotropic
<b>Pressing Time</b>	: 30 min.
<b>Shrinkage</b>	: None
<b>Temperature Resistance</b>	: -20°C to +70 °C
<b>Application Temperature</b>	: +5 °C to +35 °C

## PRODUCT

Product Type	Volume	Package
Akfix 480	310 ml	12
Akfix 480 (sausage)	600 ml	12

## DISCLAIMER

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.